



Product Benefits & Features

Keeping things clean.

With an easily removed clean and washed aluminium grease filter, you can always guarantee your cooker hood's optimal performance.



- Air extraction capacity (high/low): 220 / 140 m³/h
- Number of speeds: 3
- Cooker hood lamps type and number: LED bulb, 1
- Operation via sliding switch
- 1 Paper
- Extraction or recirculation mode possible, charcoal filter available as optional accessory for recirculation operation

Product Specification

| | | | |
|--|-------------|--|---|
| Energy Rating | D | Dimensions, HxWxD | 150-150x598x482 |
| Number of Speed Settings | 3 | Frequency (Hz) | 50 |
| Installation Type | Traditional | | OUT OF SCOPE for stand by power and off mode power |
| Size (cm) | 60 | | |
| Extraction Type - Recirculation | Yes | Other comments technical specifications | EFF57/MCEF03 is applicable on hoods until ELC number 00 starting from ELC number 01 you should apply filter EFF57F/MCFE50 |
| Extraction Type - Ducted (External) | Yes | | |
| Minimum Distance from Electric Hob (cm) | 65 | Superperforming charcoal filter compatible | NO, NO |
| Minimum Distance from Gas Hob (cm) | 65 | Product Number (PNC) | KA model |
| Cord Length (m) | 1.8 | Plug or Hardwired | Hardwired connection only |
| Voltage (V) | 220-240 | | |
| Required Fuse (A) | 10 | | |
| Charcoal Filter Type | MCFE50 | | |
| Fluid Dynamic Efficiency Rating | F | | |
| Lighting Efficiency Rating | F | | |
| Grease Filter Efficiency Rating | D | | |
| Lamp Type | LED bulb | | |
| Number of Lights | 1 | | |
| Number of Grease Filters | 1 | | |
| Min Recirculated Noise Level (dB) | 56 | | |
| Max Recirculated Noise Level (dB) | 73 | | |
| Min Recirculated Extraction Rate (m ³ /h) | 30 | | |
| Max Recirculated Extraction Rate (m ³ /h) | 75 | | |

